

Digital Receiving Scale

 Model
 Capacity
 Increments

 4040
 400 lb/180 kg
 0.5 lb/0.2 kg

Features

- Tare feature removes the weight of the container, only weighing the contents, maximum tare 50#
- Remote LCD display with 9' cord mounts on walls and is out of the way when weighing
- Rugged design handles heavy packages and containers
- Auto-off reserves battery power
- AC adapter (included) or 9V battery (not included)
- Low battery indicator alerts user when new battery is needed
- Non-skid platform with grid design keeps packages in place
- Non-skid feet assure weighing stability

Type: Receiving

Temperature Specs: $41^{\circ} - 95^{\circ}F / 5^{\circ} - 35^{\circ}C$

Power Supply: ADPT2 AC Adapter 120VAC/

9V DC or 9V battery 3.5mm mini plug (male)

Cord length - 72"

Connector length - .73" (18.5mm) – contact area 10mm

Adapter Dimensions 2.5" x 1.75"x 1.5"

Platform Dimensions: 12" x12-1/2"

Scale Dimensions: 12" x 12-1/2" x 2-1/4" **Retail Carton Dimensions:** 17-3/4" x 12-1/2" x 2-1/2"

Retail Carton Weight: 11 lb

Retail Package UPC: 0 77177 14220 8

Master Carton Quantity: 2

Master Carton Dimensions: 13-1/4" x 6-1/2" x 18-3/4"

Master Carton Weight: 22 lb

Master Carton UPC: 500 77177 14220 6

Accessories: ADPT2 Harmonized Code 8423.82.0000

Warranty: One Year Limited Warranty

pelouze:

Made to our specifications in China

©2006. Pelouze is a registered trademark of Rubbermaid Inc. 16905 Northcross Drive, Huntersville, NC 28078 | Customer Service: 800.950.9787 – Technical Support: 800.638.3722 - Fax: 888.761.8574, www.pelouzefoodservice.com