







Fair Good Better Best Superior

Atlantic Olefin® is a step above the commodity entrance mat and is intended for all medium traffic areas including entrances and lobbies. Atlantic Olefins®' durable Olefin fibers provide moisture and dirt retention at entrances and passageways; reducing slip hazards and floor care maintenance. A vinyl non-slip backing helps to minimize mat movement.

| Test | Test Description | *Results -1.17 grams (3.7%) | | |
|-------------------------------|--|---|--|--|
| ASTM D3884-01 | Abrasion Resistance | | | |
| ASTM D6540-00 | Accelerated Soiling | Based on Visual Inspection 4.0 - Vacuum Rating 5.0 - Rating After Extraction | | |
| ASTM D5252-98a | Accelerated Wear | Based on visual inspection @ 4,000 cycles Considerable change in appearance and color | | |
| CPSC FF 1-70 (ASTM D-2859) | Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material | Pass | | |
| - | Water Retention | Weight Gain = .415 gals./yd ² | | |

 $[\]hbox{*All testing of NoTrax* floor matting has been performed by an independent testing laboratory.}$

12/2014

Appearance Rating Key No change Slight change Noticeable change Considerable change Severe change







| FAIR | GOOD | BETTER | BEST | SUPERIOR |
|------|------|--------|------|----------|
| | | | | |
| | | | | |
| NR | | | | |
| | | | | |
| | | | | |

- 19 oz. face weight
- Thickness: 3/8"
- Stain resistant, 100% Olefin fibers
- Vinyl backing to reduce mat movement
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6',
 4' x 8', 4' x 10'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 3', 4', and 6' widths (up to 60')